## SUNFLEX 港

#### Profile system

- □ Glass folding door with highly thermally insulated aluminum profiles
- □ Bottom-loaded construction
- □ The construction depth of the profiles is 75 mm
- □ Option of flush or weathered bottom track
- □ The flush bottom track is particularly suitable for use in "Barrier–free dwellings" according to DIN 18 025
- □ Panel open to the inside or outside
- □ Opening of panels by sliding to one side or to both sides
- □ Flush running and guide tracks
- □ Height variations and expansions may be compensated

#### Tests

- $\Box$  U<sub>W</sub> up to 1,0 W/m<sup>2</sup>k (with glazing Ug = 0,5 W/m<sup>2</sup>k)
- □ Air permeability class 4 according to EN 1026
- □ Rain tightness class 9A according to EN 1027
- □ Resistance to wind load class B5/C4 according to EN 12210
- $\Box$  Airborne sound insulation value R<sub>W</sub> = 36 dB according to DIN EN ISO 140-3
- □ Burglar-resistance up to resistance class 2 (WK2)

#### Fittings

- □ All fittings are concealed within the profiles
- □ Low-maintenance, non-corroding and failsafe hardware components
- Locking of panels in top and bottom track and/or via mushroom head-lock engaging into the frame or adjacent panel
- □ Locking and unlocking of panels via flat handles with locking device for burglar resistance
- □ Optionally fitted with different lock types
- □ Hinges are secured against knocking-out of the pivot pins (burglar resistance)
- □ An open turn panel may be securely fixed to the adjacent panel by panel catchers

#### Running assembly

- □ Easy adjustment due to a height-adjustable carriage system
- □ The running assemblies are located above the water drainage area
- □ Low-noise, wear-, heat- and cold-resistant rollers

#### Sealing and ventilation

□ Using EPDM gaskets at two levels guarantees rain- and wind-proofness

#### Glazing

- □ A glazing configuration between 28, 40, 48 and 56 mm is possible
- □ Subsequent replacement of panes without difficulty



Testreport No.23-21/09E, No. 40-12/12 and No. 40-13/12



Testreport ATT 11.11.801.01

tested SUNFLEX Quality



Testreport 1286-001-10

SUN0617-2

### **SUNFLEX** 裀



### **SUNFLEX** <sup></sup> <sup></sup> <sup>1</sup>



#### Safety

The panels are locked and unlocked by means of a user-friendly single-handed manipulation of robust flat handles. For additional safety, different types of locks are available.



#### Mushroom head lock

For optimal tightness and burglar resistance the doorway panel (turn panel) is laterally being connected to the frame or the adjacent panel through a mushroom head lock.



#### Safety function panel catcher

In any opening position of the folding system an open turn panel may be safely locked to the adjacent panel by means of safety function panel catchers and be carried along in a controlled way.



**Burglar resistance** All external hinges are additionally secured by means of a safety screw against knocking out of the hinge bolts.



#### Proper handle series

Handles matching the profile design guarantee a harmonized overall picture of the folding system in closed state and a small panel package in open state.



Twin-Lock locking mechanism To guarantee additional safety, the optionally available twin-lock locking mechanism offers a maximum of security.



Height compensation The height of the installed folding system may be easily adjusted by a few hand grips, only – this is important in case of eventual structure sagging.



#### Assembly

The assembly shoes allow a fast and trouble-free assembly of the frame and a fine adjustment of the vertical frame profiles in the closing range.

# SUNFLEX老



Details at even panel partition in one direction



Details at even and uneven panel partition in two directions

3600 —			_		_	
3300 —				-		
3000 —				/	4	
2700 —						
2400 —					Y	
2100 —					4	
1800 —					4	
1500 —					4	
1200 —					4	
900 —					4	
600 —					1	
300			_	_		
009	- 001	800 -	- 006	1000 -	1100 -	

Ref.	Section	Description	Page
	SF75-000	Vertical-Section, glazing beads designs (softline + square - edge)	6
F	SF75-001	Vertical-Section, connection bottom track / inside folding	6
F	SF75-003	Vertical–Section, connection bottom track / outside folding	6
F	SF75-005	Vertical-Section, connection flush bottom track/ inside folding	6
F	SF75-005a	Vertical-Section, connection flush bottom track/ bottom door seal / inside folding	7
F	SF75-006	Vertical-Section, connection flush bottom track / outside folding	7
F	SF75-006a	Vertical-Section, connection flush bottom track / bottom door seal / outside folding	7
А	SF75-002	Vertical-Section, connection top track / inside folding	7
А	SF75-004	Vertical-Section, connection top track / outside folding	8
Ε	SF75-101	Horizontal-Section, blind frame - panel closing section / inside folding	8
Ε	SF75-102	Horizontal-Section, blind frame - panel closing section / outside folding	8
С	SF75-103	Horizontal-Section, panel – panel / hinge outside	8
D	SF75-104	Horizontal-Section, panel – panel / hinge inside	9
В	SF75-105	Horizontal-Section, vertical post - panel / hinge inside	9
В	SF75-106	Horizontal-Section, vertical post - panel / hinge outside	9
	SF75-107	Horizontal-Section, midrail	9
G	SF75-108	Horizontal-Section, panel – panel closing section	10
Е	SF75-109	Horizontal-Section, frame extension 35 mm	10
Ε	SF75-110	Horizontal-Section, frame extension 70 mm	10

### Panel size diagram

## SUNFLEX泡

Ref.	Section	Description	Page
E	SF75-111	Horizontal-Section, 90°- connection profile	10
E	SF75-112	Horizontal-Section, 135°- connection profile	11
D	SF75-113	Horizontal-Section, sliding post / hinge outside	11
D	SF75-121	Horizontal-Section, sliding post / hinge inside	11
D	SF75-114	Horizontal-Section, sliding post incl. strengthening / hinge outside	11
G	SF75-115	Horizontal-Section, closing section - sliding post (e.g. 1L/2R) / outside folding	12
G	SF75-116	Horizontal-Section, closing section - sliding post (e.g. 1L/2R) / inside folding	12
	SF75-117	HHorizontal-Section, blind frame – panel closing section incl. sliding post (e.g. 2R) / outside folding	12
	SF75-118	Horizontal-Section, blind frame - panel closing section incl. sliding post (e.g. 2R) / inside folding	12
	SF75-119	HHorizontal-Section, profil section - sliding post(e.g. 2L/2R) / outside folding	13
	SF75-120	Horizontal-Section, profil section - sliding post(e.g. 2L/2R) / inside folding	13

\_\_\_\_



### 



#### F $(\mathbf{F})$ 75 mm SF \* (Typ I) 2 15/16 " SF 75mm (Typ A) 2 15/16 " 28 **-** 56mm 1 1/8" - 2 3/16" 28 - 56mm 1 1/8" - 2 3/16' 2 1/8 " 72 mm 2 13/16 " 2 1/16" 53mm 13/1 54 mm OUTSIDE OUTSIDE INSIDE INSIDE 128 mm 5 1/16 " 23 mm 15/16 " 8 mm 5/16 " OKFF 8 mm 5/16 " 48 mm 14 mm 9/16 " 1 7/8 ' 3 33 mm 1 5/16 1 1 5/16 " 33 mm 15 mm 9/16 " KT 75 mm 2 15/16 Description: Description: Vertical-Section, System: SF75 Vertical-Section, System: SF75 connection flush bottom track / connection flush bottom track / Detail-No.: SF75-005a Detail-No.: SF75-006 door seal / inside folding outside folding OUTSIDE F $(\mathbf{A})$ 75 mm SF \* (Typ A) 2 15/16 " 28 - 56mm 1 1/8" - 2 3/16" 81.4mm 3 3/16 6.4mm 75mm 1/42 15/16 7/8 67mm 2 5/8 8mm 5/16 " 72 mm 2 13/16 54 mm 109mm 4 5/16 " 2 1/8 " OUTSIDE INSIDE 128 mm 5 1/16 " 8 mm 5/16 3.5mm 3/8 OKFF 42mm 1 5/8 " τi Rmm 48 mm 1 7/8 " 14 mm 9/16 " 23 mm 15/16 " 33 mm 1 5/16 " 6 n ሲ 28 - 56mm -1 1/8" - 2 3/16" 75 mm 2 15/16 INSIDE Description: Description: Vertical-Section, System: SF75 Vertical-Section, System: SF75 connection flush bottom track / connection top track / inside Detail-No.: SF75-006a folding Detail-No.: SF75-002 door seal / outside folding

**SUNFLEX**



# SUNFLEX港



## SUNFLEX泡



## SUNFLEX港



## SUNFLEX泡



## SUNFLEX港



# SUNFLEX泡

