

Profile system Glass folding door with highly thermally insulated aluminum profiles Bottom-loaded construction The construction depth of the profiles is 95 mm Rear-ventilated wooden cladding inside Option of flush or weathered bottom track The flush bottom track is particularly suitable for use in "Barrier-free dwellings" according to DIN 18 025 Panel open to the inside or outside Opening of panels by sliding to one side or to both sides Flush running and guide tracks Height variations and expansions may be compensated
Tests □ Uw up to 1,0 W/m²k (with glazing Ug = 0,5 W/m²k) □ Air permeability class 4 according to EN 1026 □ Rain tightness class 9A according to EN 1027 □ Resistance to wind load class B5/C4 according to EN 12210
□ Airborne sound insulation value R _W = 36 dB according to DIN EN ISO 140-3 □ Burglar-resistance up to resistance class 2 (WK2)
Fittings All fittings are concealed within the profiles Low-maintenance, non-corroding and failsafe hardware components Locking of panels in top and bottom track and/or via mushroom head-lock engaging into the frame or adjacent panel Locking and unlocking of panels via flat handles with locking device for burglar resistance Optionally fitted with different lock types Hinges are secured against knocking-out of the pivot pins (burglar resistance) An open turn panel may be securely fixed to the adjacent panel by panel catchers
Running assembly □ Easy adjustment due to a height-adjustable carriage system □ The running assemblies are located above the water drainage area □ Low-noise, wear-, heat- and cold-resistant rollers
Sealing and ventilation ☐ Using EPDM gaskets at two levels guarantees rain— and wind—proofness
Glazing □ Glazing configuration 40, 48 mm possible □ Subsequent replacement of panes without difficulty



Testreport No.23-21/09E, No. 40-12/12 and No. 40-13/12



Testreport ATT 11.11.801.01



tested SUNFLEX Quality



Testreport 1286-001-10

Corner angles 90°-180° with or without corner post (only available with special corner post/special design!)


Тур I




Тур А



Тур I




Тур А




Corner angles 90°-180° (only available with special corner post/special design!)

Тур I



Тур А



Other floor plan geometries upon request





Safety

The panels are locked and unlocked by means of a user-friendly single-handed manipulation of robust flat handles. For additional safety, different types of locks are available.




Mushroom head lock

For optimal tightness and burglar resistance the doorway panel (turn panel) is laterally being connected to the frame or the adjacent panel through a mushroom head lock.



Safety function panel catcher

In any opening position of the folding system an open turn panel may be safely locked to the adjacent panel by means of safety function panel catchers and be carried along in a controlled way.




Burglar resistance

All external hinges are additionally secured by means of a safety screw against knocking out of the hinge bolts.




Proper handle series

Handles matching the profile design guarantee a harmonized overall picture of the folding system in closed state and a small panel package in open state.




Twin-Lock locking mechanism

To guarantee additional safety, the optionally available twin-lock locking mechanism offers a maximum of security.



Height compensation


The height of the installed folding system may be easily adjusted by a few hand grips, only – this is important in case of eventual structure sagging.




Assembly

The assembly shoes allow a fast and trouble-free assembly of the frame and a fine adjustment of the vertical frame profiles in the closing range.





Details at even panel partition in one direction



Details at even and uneven panel partition in two directions

Panel size diagram 3600 3300 2700 2400 2100 1800 1500 1200 900 600

Ref.	Section	Description	Page
	SF75c-000	Vertical-Section, timber clad designs (classic, modern (soft), squared)	6
F	SF75c-001	Vertical-Section, connection bottom track / inside folding	6
F	SF75c-003	Vertical-Section, connection bottom track / outside folding	6
F	SF75c-005	Vertical-Section, connection flush bottom track	6
F	SF75c-005a	Vertical-Section, connection flush bottom track/ bottom door seal / inside folding	7
F	SF75c-006	Vertical-Section, connection flush bottom track / outside folding	7
F	SF75c-006a	Vertical-Section, connection flush bottom track / bottom door seal / outside folding	7
Α	SF75c-002	Vertical-Section, connection top track / inside folding	7
Α	SF75c-004	Vertical-Section, connection top track / outside folding	8
Α	A SF75c-008 Vertical-Section, strengthening profile for overhead light / inside folding		8
Α	A SF75c-009 Vertical-Section, connection top track for overhead light / inside folding		8
E	SF75c-101	Horizontal-Section, blind frame – panel closing section / inside folding	8
E	SF75c-102	Horizontal-Section, blind frame – panel closing section / outside folding	9
C	SF75c-103	Horizontal-Section, panel - panel / hinge outside	9
D	SF75c-104	Horizontal-Section, panel - panel / hinge inside	9
В	SF75c-105	Horizontal-Section, vertical post - panel / hinge inside	9
В	SF75c-106	Horizontal-Section, vertical post - panel / hinge outside	10
	SF75c-107	Horizontal-Section, midrail	10
G	SF75c-108	Horizontal-Section, panel – panel closing section	10
E	SF75c-109	Horizontal-Section, frame extension 35 mm	10
E	SF75c-110	Horizontal-Section, frame extension 70 mm	11

Folding Sliding System SF75c



Ref.	Section	Description	Page
E	SF75c-111	Horizontal-Section, 90°- connection profile	11
E	SF75c-112	Horizontal-Section, 135°- connection profile	11
D	SF75c-113	Horizontal-Section, sliding post / hinge outside	11
D	SF75c-121	Horizontal-Section, sliding post / hinge inside	12
D	SF75c-114	Horizontal-Section, sliding post incl. strengthening / hinge outside	12
G	SF75c-115	Horizontal-Section, closing section - sliding post (e.g. 1L/2R) / outside folding	12
G	SF75c-116	Horizontal-Section, closing section - sliding post (e.g. 1L/2R) / inside folding	12
	SF75c-117	Horizontal-Section, blind frame - panel closing section incl. sliding post (e.g. 2R) / outside folding	13
	SF75c-118	Horizontal-Section, blind frame - panel closing section incl. sliding post (e.g. 2R) / inside folding	13
	SF75c-119	Horizontal-Section, profil section - sliding post(e.g. 2L/2R) / outside folding	13
	SF75c-120	Horizontal-Section, profil section - sliding post(e.g. 2L/2R) / inside folding	13



